
























Product Code	Description	Features / Spec	Colour Temp / Lumens	Lamp
LED SPOT LAMP (GU10/MR16/E27/E14/B22/B15) - NON DIMMABLE				
LSB4D-G1 (Dim)	4 Watts 240V LED Globe in GU10 base	300-320lm	Warm (3000K)	
LSB5D-G1 (Dim)	5 Watts 240V LED Globe in GU10 base	400-420lm	Warm (3000K)	
LS5B-G1 or LSR5-M1 (Non Dim)	5.5W LED Globe in GU10 or 5W MR16 base	Eq to 40W Halogen	Warm (3000K) / 380lm	
LSR7 COB (Non Dim)	7W LED Globe in MR16/ GU10	Eq to 50W Halogen	Warm (3000K) 600lm /Cool (6000K) 650lm	
LSR8 (Dim)	8W LED Globe in MR16 base (Dim) Size: 50(dia)x51(h)mm	Dimmable / Dali	Warm (3000K) 600lm /Cool (6000K) 650lm	AZ 
LS8-OM (Non Dim)	8W LED Globe in GU10 base (Non Dim or Dim)	Eq to 50W Halogen	Warm (3000K) 600lm /Cool (6000K) 650lm	OM 
LS8D-OM (Dim)				
LB9-AL-C3K	9.5w Non Dimmable LED Spot Lamp with B22 or E27 Base	Eq to 75W Incandescent	Warm (3000K) / 820lm	RE 
LB9-AL-C6K			Cool (6000K) / 855lm	
LB9D-AL-C3K	9.5w Dimmable LED Spot Lamp with B22 or E27 Base	Eq to 75W Incandescent	Warm (3000K) / 820lm	
LB9D-AL-C6K			Cool (6000K) / 855lm	
LB12-AL-C3K	12W Non Dim LED Spot Lamp with B22 or E27 Base	Eq to 150W Incandescent	Warm (3000K)/1000lm	
LB12-AL-C6K			Cool (6000K) /1080lm	
LPAR38-C5K	12W PAR38 Lamp 5000K	Eq to 150W Halogen	Cool (5000K) / 800lm	CL 
GM-C035	3W LED Candle Light with 360° Beam in B15, B22, E14, E27 Lamp Base (Dimmable)	Eq to 25W Incandescent	Warm (3000K) 220lm	
GM-B050	5W LED Candle Light with 360° Beam in B15, B22, E14, E27 Lamp Base (Dimmable)	Eq to 35W Incandescent	Warm (3000K) 300lm	
LBF-G45-2W	2W LED Filament Non-Dimmable Lamp in B22/E27 Lamp Base	Eq to 20W Incandescent	200lm Size: 45(dia)x68(h)mm	
LBF-C35-4W	4W LED Filament Non-Dimmable Lamp in E14 Lamp Base	Equivalent to 40W Incandescent	380lm Size: 35(dia)x98(h)mm	
LBF-A60-4W	4W LED Filament Non-Dimmable Lamp in E27 Lamp Base	Equivalent to 40W Incandescent	380lm Size: 60(dia)x104(h)mm	
LBF-A60-6W	6W LED Filament Non-Dimmable Lamp in E27 Lamp Base	Equivalent to 60W Incandescent	380lm Size: 60(dia)x104(h)mm	
LBF-G95-6W	6W LED Filament Non-Dimmable Lamp in E27 Lamp Base	Equivalent to 60W Incandescent	380lm Size: 95(dia)x125(h)mm	
LBF-G125-6W	6W LED Filament Non-Dimmable Lamp in E27 Lamp Base	Equivalent to 60W Incandescent	380lm Size: 95(dia)x125(h)mm	
RGB 12V MR16	5W LED RGB 12V MR16 Globe + Remote Control (battery not included)		RGB	
L10D-C3K	10W DIMMABLE Retrofit DL with 60° Beam c/w LED Driver & 1mtr Flex&Plug.	Equivalent to 75W Halogen	Warm (3000K) 780lm & Cool (5000K) -800lm	








Product Code	Description	Features / Spec	Colour Temp / Lumens	Lamp
L14-CLCK4	14W LED for Circular Fluorescent Lamp Replacement	Equivalent to 28W Fluorescent	5000K 1250lm Size:190mm	
L120-CLC5	20W LED for Circular Fluorescent Lamp Replacement	Equivalent to 40W Fluorescent	5000K 1750lm Size:240mm	
DIMMER	Universal / LED Dimmer - Min 10W to 250W			

LED DOWNLIGHT KITS FOR SPOT LAMP




RFW1	Round Fixed White (Cut out size: ø70mm) exclude lamp holder	
RGW1	Round Gimble White (Cut out size: ø80mm) exclude lamp holder	
RGS1	Round Gimble Satin Chrome (Cut out size: ø80mm) exclude lamp holder	
GU10-LH	GU10 lamp holder with termination box (without Metal Support)	
GU10-LH	GU10 lamp holder with termination box (with Metal Support)	
E27 to MR16	E27 to MR16 Lamp Holder	
MR16-LH	MR16 lamp holder	


70mm to 90mm Cut Out Downlight - Dimmable

LD7-SMD-C3K SMD-C5K	LD7- White 7W DIM SMD IP44 Downlight at 100° Beam c/w LED Driver & 1mtr Flex&Plug. RA>80 (Fitting Size: ø85x50(h)mm, Cut out size: ø70mm)	Equivalent to 80W Halogen	Warm(3000K)700lm Cool(5000K)750lm	EC 
LD10-SMD-TC3K LD10-SMD-TC6K	White 9W DIM SMD IP44 IC-F Downlight at 100° Beam c/w LED Driver & 1mtr Flex&Plug. RA>80 (Fitting Size: ø115x60(h)mm, Cut out size: ø90mm).	Equivalent to 100W Halogen	Warm(3000K)750lm Cool(5000K) 800lm	CL 
LD10ED-SMD-WC3K LD10ED-SMD-WC5K	White 10W DIM SMD IP44 (Shallow 30mm height) Downlight at 100° Beam c/w LED Driver & 1mtr Flex&Plug. RA>80 (Fitting Size: ø110x30(h)mm, Cut out size: ø90mm) CCT Change Color Same Price.	Equivalent to 80W Halogen	Warm(3000K)820lm Cool(5000K)850lm	
LD10SEN-SMD-WC3K LD10SEN-SMD-WC4K LD10SEN-SMD-WC6K	White 10W SENSOR SMD IP40 Downlight at 100° Beam c/w LED Driver & 1mtr Flex&Plug. RA>80 (Fitting Size: ø110x40(h)mm, Cut out size: ø90mm)	Sensor Range 5-7mtr	Warm(3000K)800lm 4000K 820lm Cool(5000K)850lm	
LD15D-C3K-W LD15D-C5K-W	15 DIMMABLE Gimble Downlight at 60° Beam c/w LED Driver & 1mtr Flex&Plug. RA>80 (Fitting Size: ø105x105(h)mm, Cut out size: ø90mm)	Equivalent to 120W Halogen	Warm (3000K) 1275lm & Cool (5000K) 1400lm	
LD15D-C3K-BLK LD15D-C5K-BLK	15 DIMMABLE Gimble Downlight at 60° Beam c/w LED Driver & 1mtr Flex&Plug. RA>80 (Fitting Size: ø105x105(h)mm, Cut out size: ø90mm)	Equivalent to 120W Halogen	Warm (3000K) 1275lm & Cool (5000K) 1400lm	
LD15D-ENC3K	15W DIMMABLE IP20 Downlight at 36° Beam c/w LED Driver & 1mtr Flex&Plug. RA>80 (Fitting Size: ø119x103(h)mm, Cut out size: ø90mm)	Equivalent to 75W Halogen	Warm (3000K) 1200lm	EN 



Product Code	Description	Features / Spec	Colour Temp / Lumens	Lamp
Commercial Down Light or Shop Light - Cut Out from 140mm to 235mm				
LD25-COB-C3K LD25-COB-C6K	25W Gimbal Downlight (Non Dim) with Flex&Plug 60° Beam. RA>80 (Fitting: ø160mm, Cut out : ø140mm) Optional in Black for Additional \$3.0+gst	60W MH Replacement	Warm(3000K)2200lm / Cool(6000K) 2300lm	
LD20-EC3K LD20-EC6K	20W Downlight (Non Dim) with 1.2m Flex&Plug 120° Beam. RA>80 (Fitting: ø195mm, Cut out : ø175mm)	50W MH Replacement	Warm(3000K)1700lm / Cool(6000K) 1800lm	
LD30-C4K LD30-C6K	30W Downlight (Non Dim) with 1.2m Flex&Plug 120° Beam. RA>80 (Fitting: ø222mm, Cut out: ø200mm)	75W MH Replacement	Warm(4000K)2600lm / Cool(6000K) 2700lm	
LDP15-C6K	15W SMD Slimline Downlight (Non Dim) with Flex&Plug 100° Beam (Fitting ø170(dia) x12(h)mm, Cut out: ø155mm)	 Surface Mounted +\$5.0+gst	Cool (6000K) / 1350lm	
LDP20-C6K	20W SMD Slimline Downlight (Non Dim) with Flex&Plug 100° Beam (Fitting ø225(dia) x12(h)mm, Cut out: ø205mm).		Cool (6000K) / 1800lm	
LD50-SMD-C5K	50W SMD Slimline Downlight (Non Dim) with Flex&Plug 100° Beam (Fitting: ø245(dia) x56(h)mm, Cut out: ø205-230mm)	150W MH Replacement	Cool (5000K) / 4320lm	
LD50-SMD-ACC1	Optional: 235mm Extension plate for 50W SMD slimline downlight (For Fitting Size: 245mm. Cut Out Size ø320mm)			

Commercial Down Light or Shop Light - Cut Out from 140mm to 235mm				
LOYS-CL20	20W Oyster Light 3000K/5000K (Size: 330(dia)x110(h)mm	50W MH Replacement	Warm(3000K) or Cool 5000K 1400lm	CL 
LOYS-CL20SEN	20W SENSOR Oyster Light 3000K/5000K IP44 Size: 330(dia)x110(h)mm	50W MH Replacement	Warm(3000K) or Cool 5000K 1400lm	CL 
LSL-TW30 (Cool Only)	30W LED COB Gimble Round Shop Lighter 350° twist & 45° Beam Angle.Flex&Plug (Fitting: ø190mm, Cut out: ø175mm)	75W MH Replacement	Cool(6000K) 2700lm	
LSL-TW48 (Warm / Cool)	48W LED COB Gimble Round Shop Lighter 350° twist & 45° Beam Angle.Flex&Plug (Fitting: ø190x175(h)mm, Cut out: ø165mm)	150W MH Replacement	Warm (3000K) 3800lm / Cool(5500K) 3900lm	EN 
LSL-40-SMD-C3K LSL-40-SMD-C4K LSL-40-SMD-C6K	40W LED SMD Shop Lighter in frosted glass. RA>80. Flex & Plug: (Fitting Size: 240x156mm, Cut Out Size: 225x125mm)	120W MH Replacement	Warm (3000K) 3200lm/ Warm (4000K)3300lm / Cool (6000K) 3400lm	CL 

LED BATTEN (SLIM/WEATHERPROOF) AND LED TUBE				
LT8-6H-9	9W 600mm length	Complete with fuse to replace existing starter	6000K (800lm)	
LT8-12H-18	18W 1200mm length		6000K (1440lm)	
LT8-15H-27	27W 1500mm length		6000K (2200lm)	
LT8WP-218	2x18W LED T8 Tube in Weatherproof fitting (no flex and plug)	IP65	Cool (6000K) / 2x1440lm	
LLN-40IP-C6K	40W Slimline Linear Light with Weatherproof: Size: 36x80x1200mm	IP65	Cool (6000K) / 3600lm	

Product Code	Description	Features / Spec	Colour Temp / Lumens	Lamp
LLN-20-C6K	20W Slimline Linear light Size 36x80x600mm	1800lm	Cool (6000K)	
LLN-40-C6K	40W Slimline Linear Light Size: 36x80x1200mm	3600lm	Cool (6000K)	
LLN-40SEN-C6K	40W Slimline Linear Light with Microwave Sensor. Dim Down to 10% or 50%. Size: 36x80x1200mm	3600lm w/ microwave sensor	Cool (6000K)	






LED LINKABLE IN T5

LT5-CA-Z04B	4W Linkable 26(w)x35(h)x315(l) mm	Non Dmmable with Individual Switch	3000K/6000K 320lm/ 360lm	CL  
LT5-CA-Z08B	8W Linkable 26(w)x35(h)x580(l) mm		3000K/4000K/6000K 550lm/ 570lm/600lm	
LT5-CA-Z12B	12W Linkable 26(w)x35(h)x880(l) mm		3000K/4000K/6000K 1000lm/1050lm/1100lm	
LT5-CA-Z15B	15W Linkable 26(w)x35(h)x1180(l) mm		3000K/4000K/6000K 1165lm/1220lm//1275lm	
LT5-ACC-F&P	1.2mtr flex and plug for linkable T5			
LT5-ACC-M&F	150mm length male & female joint plug			

LED PANEL LIGHT (OPTIONAL FOR SURFACE MOUNT KITS)

LGRID3x6-F24	24W LED Surface Panel Grid Light 2200lm, 300x600x15(h)mm	IP20	6000k	NI 
LGRID6x6-F36	36W LED Surface Panel Grid Light 3200lm, 600x600x15(h)mm	IP20	4000k/ 6000k	
LGRID3x12-F36	36W LED Surface Panel Grid Light 3200lm, 300x1200x15(h)mm	IP20	4000k/ 6000k	
LGRID3x12-F60	60W LED Panel Grid Light 4800lm, 300x1200x15(h)mm	IP20	6000k	
LGRID3x12-F40	40W LED Panel Grid Light 3600lm, 300x1200x15(h)mm	IP20	4000k/ 6000k	
LGRID-MOUNT	Surface Mounting Kits - 600x600mm or 300x1200mm			NI 
LGRID-HANG1	1.5mtr Hanging Kit (2pcs per set)			U 

Product Code	Description	Features / Spec	Colour Temp / Lumens	Lamp
Commercial Flood Light and High Bay - 2 Year Warranty				
LFL-20SL-C6K	20W LED Slimline SMD Flood Light 185wx145hx30d mm	Size: IP65 with Flex & Plug	Cool (6000K) 2000lm	
LFL-20SLE-C6K	20W LED ECO SMD Flood Light 173wx140hx40d mm	Size: IP65 with Flex & Plug	Cool (6000K) 1800lm	
LFL-30SLE-C6K	30W LED ECO SMD Flood Light 235wx185hx40d mm	Size: IP65 with Flex & Plug	Cool (6000K) 2700lm	
LFL-50SLE-C6K	50W LED ECO SMD Flood Light 285wx240hx45d mm	Size: IP65 with Flex & Plug	Cool (6000K) 4500lm	
LFL-70SLE-C6K	70W LED ECO SMD Flood Light 320wx295hx60d mm	Size: IP65 with Flex & Plug	Cool (6000K) 6300lm	
LFL-2x13TWIN-C6K	2x13W LED Twin Flood Light 235wx185hx40d mm	Size: IP65 with Flex & Plug	Cool (6000K) 2700lm	
LFL-30SLESEN-C6K	30W LED ECO Sensor SMD Flood Light 235wx185hx40d mm	Size: IP65 with Flex & Plug	Cool (6000K) 2700lm	
LFL-70SLESEN-C6K	70W LED ECO Sensor SMD Flood Light 320wx295hx60d mm	Size: IP65 with Flex & Plug	Cool (6000K) 6300lm	
LFL-2x13SEN-C6K	2x13W LED Twin Sensor Flood Light 235wx185hx40d mm	Size: IP65 with Flex & Plug	Cool (6000K) 2700lm	
LFL-RGB-20	20W 240V RGB Flood light	IP65 with Flex & Plug	RGB	
LFL-RGB-50	50W 240V RGB Flood Light			

Commercial Premium Flood Light and High Bay - 3 Year Warranty					
LFL-70P-C6K	70W LED SMD Flood Light mm	Size: 250wx300hx54d	Replacement for 150W Metal Halide	Cool (6000K) / 10000lm	EN 
LFL-100P-C6K	100W LED SMD Flood Light mm	Size: 295wx345hx54d	Replacement for 250W Metal Halide	Cool (6000K) / 10000lm	
LFL-150P-C6K	150W LED SMD Flood Light with MW Driver	Size:300wx365hx54d mm	Replacement for 300W Metal Halide	Cool (6000K) / 15,000lm	
LFL-200P-C6K	200W LED COB Flood Light IP65 with MW Driver	Size:360wx400hx54d mm	Replacement for 500W Metal Halide	Cool (6000K) / 20000lm	
LFL-400P-C6K (by LUXTRONIC)	400W Philips Lumiled LED Flood Light Size:593wx606hx117d mm Driver and Power Plug	IP65 with MW	Replacement for 1000W Metal Halide	Cool (6000K) / 44000lm 1000W Metal Halide Replacement.	
LHB-150G010-C6K	150W LED UFO Type Low/High Bay 120° Beam Angle (Fitting Size: ø350mmx160h) IP65		Replacement for 400W MH	3 Years Warranty with Nichia Chip and Meanwell Driver. 17250lm	
LLB-3312-C6K	150W LED Canopy Low Bay 90o Beam Angle (Fitting Size: 597x597x40(h)mm) IP65		Replacement for 400W Metal Halide	Cool (5000K) / 15,750lm	AC 
LLB-3316-C6K	200W LED Canopy Low Bay 90o Beam Angle (Fitting Size: 597x597x40(h)mm) IP65		Replacement for 500W Metal Halide	Cool (5000K) / 21,000lm	