









Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
<b>LED SPOT LAMP (GU10/MR16/E27/E14/B22/B15) - NON DIMMABLE</b>				
LSB4D-G1 (Dim)	4 Watts 240V LED Globe in GU10 Dim	 <b>3000K Only</b>	Dimmable	Warm (3000K)
LSB5D-G1 (Dim)	5 Watts 240V LED Globe in GU10 Dim		Dimmable	Warm (3000K)
LSR5-M1 (Non Dim)	5W LED Globe MR16 Non-Dim	 <b>3000K Only</b>	Eq to 40W Halogen	Warm (3000K) / 380lm
LSR7 COB (Non Dim)	7W LED Globe in MR16/ GU10 Non Dim	 <b>3000K/6000K</b>	Eq to 50W Halogen	Warm (3000K) 600lm /Cool (6000K) 650lm
LS6-Primsal (GU10)	<b>6W GU10</b> LED Globe Size: 50(dia)x51(h)mm Dim	 <b>3000K</b>	Dimmable	Warm (3000K) 600lm
LS6-Primsal (MR16 or GU10)	<b>6W MR16</b> LED Globe Size: 50(dia)x51(h)mm Non-Dim	 <b>3000K</b>	Non Dim	Warm (3000K) 600lm /Cool (5000K) 650lm
LS8-OM (Non Dim)	<b>8W MR16/GU10</b> LED Globe Non-Dim	 <b>3000K/6000K</b>	Non Dim	Warm (3000K) 600lm /Cool (5000K) 650lm
LS8D-OM (Dim)	<b>8W MR16</b> LED Globe Size: 50(dia)x51(h)mm Dim	 <b>3000K/6000K</b>	Dimmable	Warm (3000K) 600lm /Cool (5000K) 650lm
LB6-OM-A50C3K	<b>6w A50</b> Non Dimmable LED Globe/Lamp with B22 or E27 Base	 <b>OM</b> <b>3000K/5000K</b>	Eq to 55W Incandescent	Warm (3000K) / 520lm
LB6-OM-A50C5K				Cool (5000K) / 540lm
LB7-CLA-A60 C3K	<b>7w A60</b> Non Dimmable LED Globe/Lamp with B22 or E27 Base	 <b>CLA</b> <b>3000K/5000K</b>	Eq to 55W Incandescent	Warm (3000K) / 520lm
LB6-CLA-A60C5K				Cool (5000K) / 540lm
LB9-CLAT40-C3K	<b>9w T40</b> Non Dimmable LED Globe/Lamp with B22 or E27 Base	 <b>3000K/5000K</b>	Eq to 75W Incandescent	Warm (3000K) / 820lm
LB9-CLAT40-C6K				Cool (5000K) / 855lm
LB9-AL-C3K	<b>9.5w A60</b> Non Dimmable LED Spot Lamp with B22 or E27 Base	 <b>RE 3000K/5000K</b>	Eq to 75W Incandescent	Warm (3000K) / 820lm
LB9-AL-C6K				Cool (6000K) / 855lm
LB12-AL-C3K	<b>12w A70</b> Non Dim LED Spot Lamp with E27 Only	 <b>3000K/5000K</b>	Eq to 150W Incandescent	Warm (3000K) / 1000lm
LB12-AL-C6K				Cool (6000K) / 1080lm

Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
LPAR38-C5K	<b>Out of stock</b> 12W PAR38 Lamp 5000K	CL 	Eq to 150W Halogen Par Lamp	Cool (5000K) / 800lm
GM-C035	3W LED Candle Light with 360° Beam in B15, B22, E14, E27 Lamp Base (Dimmable)	 3000K	Eq to 25W Incandescent	Warm (3000K) 220lm
GM-B050	5W LED Candle Light with 360° Beam in B15, B22, E14, E27 Lamp Base (Dimmable)	 3000K	Eq to 35W Incandescent	Warm (3000K) 300lm
LBF-G45-2W	<b>2W G45 NonDim</b> LED Filament Non-Dimmable Lamp in B22/E27	 3000K	Eq to 20W Incandescent	200lm Size: 45(dia)x68(h)mm
LBF-C35-4W	<b>4W Candle Dim</b> LED Filament Dimmable Lamp in E14/E27	 3000K	Equivalent to 40W Incandescent	380lm Size: 35(dia)x98(h)mm
LBF-A60-4W	<b>4W A60 NonDim</b> LED Filament Non-Dimmable Lamp in E27	 3000K	Equivalent to 40W Incandescent	380lm Size: 60(dia)x104(h)mm
LBF-A60-6W	<b>6W A69 Dim</b> LED Filament Dimmable Lamp in E27	 3000K	Equivalent to 60W Incandescent	380lm Size: 60(dia)x104(h)mm
LBF-G95-6W	<b>6W G95 Dim</b> LED Filament Dimmable Lamp in E27	 3000K	Equivalent to 60W Incandescent	380lm Size: 95(dia)x125(h)mm
LBF-G125-6W	<b>6W G125 Dim</b> LED Filament Dimmable Lamp in E27	 3000K	Equivalent to 60W Incandescent	380lm Size: 125(dia)x125(h)mm
RGB 12V MR16	5W LED RGB 12V MR16 Globe + Remote Control	RGB 		RGB
G4 MR11	<b>6W G4 12VDC</b> G4 3000K / 6000K	G4 		G4
G4 MR11	<b>4W G4 12VDC</b> G4 3000K / 6000K	G4 COB 		G4
G9	<b>9W G9 240V</b> 3000K / 6000K	G9  G9		G9













Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
LB6-DC-A50	<b>6w A50 Non Dimmable LED Globe in E27 Base 3000K/6000K</b>	12V-24V 		G9
LB9-DC-A60 C3K	<b>9w A60 Non Dimmable LED Globe/Lamp in E27</b>	12V-24V 	Eq to 55W Incandescent	Warm (3000K) / 820lm
LB9-DC-A60 C6K				Cool (6000K) / 855lm
LB6-DC-CORN	<b>9w Corn 12-24V NonDim LED Globe in E27 Base 3000K/6000K</b>	12V-24V 		Warm (3000K) 780lm & Cool (5000K) -800lm
L10D-C3K	10W DIMMABLE Retrofit DL with 60° Beam c/w LED Driver & 1mtr Flex&Plug.		Equivalent to 75W Halogen	Warm (3000K) 780lm & Cool (5000K) -800lm
<b>*NEW Tri-Color*</b> L120-CLC5	20W LED for Circular Fluorescent Lamp Replacement		Equivalent to 40W Fluorescent	5000K 1750lm Size:240mm
<b>LED DOWNLIGHT KITS FOR SPOT LAMP</b>				
RFW1	Round Fixed White (Cut out size: <b>ø70mm</b> ) exclude lamp holder			
RFS1 (Sold Out)	Round Fixed Satin Chrome (Cut out size: <b>ø70mm</b> ) exclude lamp holder			
RGW1	Round Gimble White (Cut out size: <b>ø80mm</b> ) exclude lamp holder			
RGS1	Round Gimble Satin Chrome (Cut out size: <b>ø80mm</b> ) exclude lamp holder			
GU10-LH	GU10 lamp holder with termination box (without Metal Support)			
GU10-LH	GU10 lamp holder with termination box (with Metal Support)			
E27 to MR16	E27 to MR16 Lamp Holder			
MR16-LH	MR16 lamp holder			
<b>70mm to 90mm Cut Out Downlight - Dimmable</b>				
LD10-SMD-3CCT	<b>10W 3CCT 70mm Cut</b> DIM SMD WHITE IP44 100° Beam c/w Driver & Flex&Plug. RA>80 (Fitting Size: ø85x 50(h)mm, Cut out size: ø70mm)	70mm-BD 	Equivalent to 80W Halogen	3CCT : 3000K to 4000K to 5000K 820lm to 850lm

Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
LD10-SMD-3CCT	<b>10W 3CCT 70mm or 90mm Cut</b> DIM SMD WHITE IP44 100° Beam c/w Driver & Flex&Plug. RA>80 (Fitting Size: ø110x 70(h)mm, Cut out size: ø90mm)	<b>90mm-TB</b> 	Equivalent to 80W Halogen	3CCT : 3000K to 4000K to 5000K 820lm to 850lm
LD10D-SMD-WC3K LD10D-SMD-WC5K	<b>10W DIM</b> SMD IP44 IC-F Downlight at 100° Beam c/w LED Driver & Flex&Plug. RA>80 (Fitting Size: ø115x 60(h)mm, Cut out size: ø90mm).	<b>90mm-TB</b> 	Equivalent to 80W Halogen	Warm(3000K)750lm Cool(5000K) 800lm
LD10CLA-SMD-3CCT (shallow 30mm height)	<b>10W 3CCT(via Light Switch) DIM</b> SMD IP44 100° Beam c/w LED Driver & Flex&Plug. RA>80 (Fitting Size: ø110x 30(h)mm, Cut out size: ø90mm)		Equivalent to 80W Halogen	3CCT : 3000K to 4000K to 5000K 820lm to 850lm
LD10CLA-SMD-3CCT (shallow 30mm height)	<b>10W 3CCT</b> DIM SMD IP44 100° Beam c/w LED Driver & Flex&Plug. RA>80 (Fitting Size: ø110x 30(h)mm, Cut out size: ø90mm)		Equivalent to 80W Halogen	3CCT : 3000K to 4000K to 5000K 820lm to 850lm
LD10CLA-SMD-3CCT (shallow 30mm height)	<b>10W 3CCT</b> DIM SMD IP44 100° Beam c/w LED Driver & Flex&Plug. RA>80. Size: ø110x 30(h)mm, Cut out size: ø90mm)		Equivalent to 80W Halogen	3CCT : 3000K to 4000K to 5000K 820lm to 850lm
LD10D-COB-TBC3K LD10D-COB-TBC5K	<b>10W DIM</b> COB IP42 Downlight at 60° Beam c/w LED Driver & Flex&Plug. RA>80 (Fitting Size: ø100x 50(h)mm, Cut out size: ø80mm)	<b>Telbix COB</b> 	Equivalent to 80W Halogen	Warm(3000K)820lm Cool(5000K) 860lm
LD12D-COB-BDC3K LD12D-COB-BDC5K	<b>10W DIM</b> SMD IP44 IC-F Downlight at 100° Beam c/w LED Driver & Flex&Plug. RA>80 (Fitting Size: ø115x 60(h)mm, Cut out size: ø90mm)	<b>90mm-BD</b> 	Equivalent to 80W Halogen	Warm(3000K)750lm Cool(5000K) 800lm
LD10S-SMD-WC3K LD10S-SMD-WC6K	<b>10W SENSOR Movement</b> SMD IP42 Sensor 100° Beam c/w LED Driver & Flex&Plug. RA>80 (Fitting Size: ø110x 40(h)mm, Cut out size: ø90mm)	 3000K/6000K	Sensor Range 5-7mtr	Warm(3000K)820lm Cool(6000K)850lm











Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
LD10S-SMD-WC3K LD10S-SMD-WC6K	<b>10W SENSOR Dusk to Down</b> SMD IP42 Sensor 100° Beam c/w LED Driver & Flex&Plug. RA>80 (Fitting Size: ø110x 40(h)mm, Cut out size: ø90mm)	 3000K/6000K	Sensor Range 5-7mtr	Warm(3000K)820lm Cool(6000K)850lm
LD18S-SMD-WC4K LD18S-SMD-WC6K	<b>18W SENSOR Movement</b> <b>Surface</b> SMD IP42 Sensor 100° Beam c/w LED Driver & w/o Flex&Plug. RA>80 (Fitting Size: ø200x 50(h)mm)		Sensor Range 5-7mtr	4000K 1420lm Cool(6000K)1440lm
<b>10W to 15W LED Modular Downlight (Please refer to Architectural DL Price list)</b>				
LDL-BD-25ENSA	<b>25W Gimble DIMMABLE</b> IP20 Downlight at 35° Beam c/w LED Driver & 1mtr Flex&Plug. RA>80 (Fitting Size: ø142x 118(h)mm, Cut out size: ø110mm)	EN 	Equivalent to 60W Halogen	3000K/6000K 1800lm
<b>Commercial Down Light or Shop Light - Cut Out from 140mm to 235mm</b>				
LD25-COB-C3K LD25-COB-C6K	<b>25W</b> Gimbal Downlight (Non Dim) with Flex&Plug 60° Beam. RA>80 (Fitting: ø160mm, Cut out : ø140mm )	 3000K/6000K	60W MH Replacement	Warm(3000K)2200lm / Cool(6000K) 2300lm
LD25-COB-C3K LD25-COB-C6K	<b>25W</b> Gimbal Downlight (Non Dim) with Flex&Plug 60° Beam. RA>80 (Fitting: ø160mm, Cut out : ø140mm )	 3000K/6000K	60W MH Replacement	Warm(3000K)2200lm / Cool(6000K) 2300lm
LD20-EC3K EC6K	LD20- <b>20W</b> Downlight (Non Dim) with 1.2m Flex&Plug 120° Beam. RA>80 (Fitting: ø195mm, Cut out : ø175mm )	 3000K/6000K	50W MH Replacement	Warm(3000K)1700lm / Cool(6000K) 1800lm
LD30-C4K C6K	LD30-30W Downlight (Non Dim) with 1.2m Flex&Plug 120° Beam. RA>80 (Fitting: ø222mm, Cut out: ø200mm )	 3000K/4000K/6000K	75W MH Replacement	Warm(4000K)2600lm / Cool(6000K) 2700lm
LD15-JDSC6K	15W SMD Slimline Downlight (Non Dim) with Flex&Plug 100° Beam (Fitting ø135(dia) x40(h)mm, Cut out: ø115mm )	 3000K/5000K		Cool (6000K) / 1350lm








Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
LDP15-C6K	<b>15W</b> SMD Slimline Downlight (Non Dim) with Flex&Plug 100° Beam (Fitting ø170(dia) x12(h)mm, Cut out: ø155mm )	 6000K		Cool (6000K) / 1200lm
LDP20-C6K	<b>20W</b> SMD Slimline Downlight (Non Dim) with Flex&Plug 100° Beam (Fitting ø225(dia) x12(h)mm, Cut out: ø205mm )	 6000K		Cool (6000K) / 1600lm
LDP20-C6K (Surface)	20W SMD Surface DL (Non Dim) w/o Flex&Plug 100° Beam (Fitting ø225(dia) x12(h)mm ).	 6000K		Cool (6000K) / 1600lm
<b>*NEW Tri-Color*</b> LD50-SMD-3CCT	50W SMD Slimline Downlight (Non Dim) with Flex&Plug 100° Beam (Fitting: ø245(dia) x56(h)mm, Cut out: ø205-230mm )	 6000K	150W MH Replacement	Cool (5000K) / 4320lm
LD50-SMD-ACC1	Extension Plate: 50W SMD slimline downlight. For Fitting Size: 245mm. New Cut Out Size ø320mm)			
LOYS-TB16	<b>16W</b> Oyster Light 5000K (Size: 290(dia)x83(h)mm	 TB 5000K		Cool (5000K) / 1000lm
LOYS-TB22	22W Oyster Light 5000K (Size: 335(dia)x85(h)mm	 TB 5000K		Cool (5000K) / 1500lm
LOYS-TB28	28W Oyster Light 5000K (Size: 405(dia)x93(h)mm	 TB 5000K		Cool (5000K) / 1500lm
LSL-TW30 (Cool Only)	30W LED COB Gimble Round Shop Lighter 350° twist & 45° Beam Angle.Flex&Plug (Fitting: ø190x175(h)mm, Cut out: ø170mm )	 6000K	75W MH Replacement	Cool(6000K) 2700lm
LSL-TW38 (Warm / Cool)	38W LED COB Gimble Round Shop Lighter 350° twist & 45° Beam Angle.Flex&Plug (Fitting: ø195x175(h)mm, Cut out: ø165mm )	 EN 3000K/5500K	150W MH Replacement	Warm (3000K) 3800lm / Cool(5500K) 3900lm
LSL-40-SMD-C3K LSL-40-SMD-C4K LSL-40-SMD-C6K	40W LED SMD Shop Lighter in frosted glass. RA>80. Flex & Plug: (Fitting Size: 240x156mm, Cut Out Size: 225x125mm)	 CL/BD 4000K/6000K	120W MH Replacement	Warm (3000K) 3200lm/ Warm (4000K)3300lm / Cool (6000K) 3400lm


Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
<b>LED BATTEN (SLIM/WEATHERPROOF) AND LED TUBE</b>				
LT8-6H-9	<b>9W</b> 600mm length	 3000K/4000K/6000K	Complete with fuse to replace existing starter	6000K (800lm)
LT8-12H-18	<b>18W</b> 1200mm length			6000K (1440lm)
LT8-15H-27	<b>27W</b> 1500mm length			6000K (2200lm)
LT8WP-118	<b>1x18W</b> LED T8 Weatherproof Batten (no flex&plug) Size:1200x55(w)x80(h)mm	 5000K	IP65	Cool (6000K) / 2x1440lm
LT8WP-218	<b>36W</b> LED T8 Weatherproof Batten (no flex&plug) Size:1200x110(w)x80(h)mm	 5000K	IP65	Cool (6000K) / 2x1440lm
LT8WP-218	<b>36W</b> LED Weatherproof Emergency Batten (no flex&plug) ize:1200x110(w)x80(h)mm	 5000K	IP65	Cool (6000K) / 3600lm
LLN-40IP-C6K <b>(Discontinue 05/2020)</b>	40W Slimline Linear Light with Weatherproof: Size: 36x80x1200mm	 6000K Only	IP65	Cool (6000K) / 3600lm
LLN-20-C4K	20W Slimline Linear light Size 36x80x600mm	 4000K (only)	1800lm	4000K only
LLN-36SLIM-3CCT	<b>36W 3CCT</b> Surface Slimline Linear Light Size: 30x75x1200mm	 3CCT	3600lm	3000K to 4000K to 6000K
LLN-40JET-C5K	<b>40W</b> Slimline Linear Light Size: 30x75x1200mm	 5000K Only	3600lm	5000K
LLN-40SEN-C6K	40W Slimline Linear Light with Microwave Sensor. Dim Down to 10% or 50%. Size: 36x80x1200mm	 6000K Only	3600lm w/ microwave sensor	Cool (6000K)
<b>LED PANEL LIGHT (OPTIONAL FOR SURFACE MOUNT KITS)</b>				
LGRID3x6-F24	<b>24W</b> LED Surface Panel Grid Light 2200lm NonDim, 300x600x15(h)mm <b>6000K Only</b>	 OPT 3000K/5000K	IP20	6000k

Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
<b>*New Tri-Color*</b> LGRID6x6-F40	<b>40W</b> LED Surface Panel Grid Light 3200lm NonDim, 600x600x15(h)mm <b>3000K to 4000K to 6000K</b>		IP20	4000k/ 5000k
LGRID3x12-F40	<b>40W</b> LED Surface Panel Grid Light 3200lm NonDim, 300x1200x15(h)mm <b>3000K to 4000K to 5000K</b>	 4000K/5000K	IP20	4000k/ 5000k
LGRID3x12-F60	<b>54W</b> LED Panel Grid Light 4800lm, 300x1200x15(h)mm	 4000K/5000K	IP20	6000k
LGRID-MOUNT	Surface Mounting Kits - 600x600mm or 300x1200mm			
LGRID-HANG1	1.5mtr Hanging Kit (2pcs per set)			
<b>Commercial Flood Light and High Bay - 2 Year Warranty</b>				
LFL-15SL-TBC5K	<b>15W</b> LED Slim SMD Flood Light Size:185wx145hx30d mm	 5000K Only	IP65	Cool (5000K) 1350lm
LFL-25SL-TBC5K	<b>25W</b> LED Slim SMD Flood Light Size: 228wx168hx38d mm	 5000K Only	IP65	Cool (5000K) 21250lm
LFL-20SLE-C6K	<b>20W</b> LED ECO SMD Flood Light Size: 173wx140hx40d mm	 6000K Only	IP65 with Flex & Plug	Cool (6000K) 1800lm
LFL-30SLE-C6K	<b>30W</b> LED ECO SMD Flood Light Size: 173wx140hx40d mm	 4000K/6000K	IP65 with Flex & Plug	Cool (6000K) 2700lm
LFL-30SLE-24VC6K	<b>30W 24V DC</b> LED ECO SMD Flood Light Size: 173wx140hx40d mm	 24VDC 4000K Only	IP65 with Flex & Plug	Cool (6000K) 2700lm
LFL-50SLE-C6K	<b>50W</b> LED ECO SMD Flood Light Size: 285wx240hx45d mm	 6000K Only	IP65 with Flex & Plug	Cool (6000K) 4500lm
LFL-70SLE-C6K	<b>70W</b> LED ECO SMD Flood Light Size: 320wx295hx60d mm	 6000K Only	IP65 with Flex & Plug	Cool (6000K) 6300lm



Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
LFL-100SLE-C6K	<b>100W</b> LED ECO SMD Flood Light Size:320wx295hx60d mm	 6000K Only	IP65 with Flex & Plug	Cool (6000K) 8500lm
LFL-1x10-TBC5K	<b>1x10W</b> LED Twin Flood Light E27 Base	 5000K Only	IP65 w/o wire	Cool (5000K) 800lm
LFL-2x10-TBC5K	<b>2x10W</b> LED Twin Flood Light E27 Base Size: 235wx185hx40d mm	 5000K Only	IP65 w/o wire	Cool (5000K) 1600lm
LFL-2x10-TBC5K	<b>2x10W</b> LED Twin Flood Light Size: 235wx185hx40d mm	 5000K Only	IP65 w/o wire	Cool (5000K) 1600lm
LFL-2x15-PRC6K	<b>2x15W</b> LED Twin Flood Light Size: 235wx185hx40d mm	 5000K Only	IP65 w/o wire	Cool (6000K) 2700lm
LFL-2x15SEN-PRC6K	<b>2x15W</b> LED Twin Sensor Flood Light Size: 235wx185hx40d mm	 5000K Only	IP65 w/o wire	Cool (6000K) 2700lm
LFL-30SLESEN-C6K	<b>30W</b> LED ECO Sensor SMD Flood Light Size: 235wx185hx40d mm	 30W	IP65 with Flex & Plug	Cool (6000K) 2700lm
LFL-70SLESEN-C6K	<b>70W</b> LED ECO Sensor SMD Flood Light Size: 320wx295hx60d mm	 70W	IP65 with Flex & Plug	Cool (6000K) 6300lm
LFL-30SLE-24VC6K	<b>30W 24V DC</b> LED ECO SMD Flood Light Size: 173wx140hx40d mm	 4000K Only	IP65 with Flex & Plug	Cool (6000K) 2700lm
LFL-30SLE-12-24V	<b>30W 12-24V DC</b> LED ECO SMD Flood Light Size: 160wx120hx40d mm	 3000K/6000K	IP65 with Flex & Plug	Cool (6000K) 2700lm

Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
LFL-10RGB-12V	<b>10W 12V RGB</b> Flood light +Remote		IP65 with Flex & Plug	RGB
LFL-20RGB-12V	<b>20W 12V RGB</b> Flood light + Remote			
LFL-30RGB-24V	<b>30W 24V RGB</b> Flood light +Remote			
LFL-30RGB-240V	<b>30W 240V RGB</b> Flood Light +Remote			
<b>Commercial Premium Flood Light and High Bay - 3 Year Warranty</b>				
<b>*On Special*</b> LFL-100P-JDSC6K	<b>100W</b> LED SMD Flood Light Size: 295wx345hx54d mm <b>3YRS Warranty</b>		Replacement for 250W Metal Halide	Cool (6000K) / 10000lm
LFL-150P-C6K	<b>150W</b> LED SMD Flood Light Size:300wx365hx54d mm with MW Driver		Replacement for 300W Metal Halide	Cool (6000K) / 15,000lm
LFL-200P-C6K	<b>200W</b> LED COB Flood Light Size:360wx400hx54d mm IP65 with MW Driver <b>3 YRS Warranty</b>		6000K Only 3 YRS Warranty	Replacement for 500W Metal Halide
LFL-400P-C6K (by LUXTRONIC)	<b>400W</b> Philips Lumiled LED Flood Light Size:593wx606hx117d mm IP65 with MW Driver and Power Plug		Replacement for 1000W Metal Halide	Cool (6000K) / 44000lm 1000W Metal Halide Replacement.
<b>*On Special*</b> LHB-100-C6K	<b>100W</b> LED High Bay 100° Beam Angle (Fitting Size: ø360mmx300h) IP20 with Flex & Plug. <b>Acrylic reflector Additional \$25+gst</b>		Replacement for 300W MH	Heat sink Technolgy Cool (6000K)10000lm
LHB-150-UFOC6K	<b>150W</b> LED Slim High Bay IP65 Size:ø300wx160hmm		Replacement for 300W Metal Halide	Cool (6000K) / 15,000lm
LFL-200-UFOC6K	<b>200W</b> LED Slim High Bay IP65 Size:ø300wx160hmm		3 YRS Warranty	Replacement for 500W Metal Halide
LLB-6670-C6K (Food processing Factory)	<b>70W</b> LED Canopy Low Bay 90° Beam Angle (Fitting Size: 597x597x40(h)mm) IP65 with power plug		AC Replacement for 200W Metal Halide	Cool (5000K) / 7,000lm

Product Code	Description	Lamp	Features / Spec	Colour Temp / Lumens
LLB-66150-C6K (Food Processing Factory)	<b>150W</b> LED Canopy Low Bay 90° Beam Angle (Fitting Size: 597x597x40(h)mm) IP65 with power plug	 5000K 3 YRS Warranty	Replacement for 400W Metal Halide	Cool (5000K) / 15,000lm
LLB-66200-C6K (Food Processing Factory)	<b>200W</b> LED Canopy Low Bay 90° Beam Angle (Fitting Size: 597x597x40(h)mm) IP65 with power plug		Replacement for 500W Metal Halide	Cool (5000K) / 20,000lm