























<b>LED Strip / Driver / Profile / Controller</b>							
Model No	LED Type	LED Qty	Color	Per Pack Length x Width	Voltage	Power (per mtr)	Lumen per Chip
<b>12V 60Leds/Mtr SMD2835</b>							
LSTR1-20-60C3K	SMD3825 IP20	60pcs / M	3000K Warm White	5000x8mm	DC12V	6W	12lm
LSTR1-20-60C6K			6000K White				12lm
LSTR1-20-S60C3K or C6K	SMD2835 IP20 "S" Bendable Strip	60pcs / M	3000K / 6000K	5000x8mm	DC12V	6W	12lm
<b>12V 120Leds/Mtr SMD2835</b>							
LSTR1-20-120C3K	SMD2835 IP20	120pcs / M	3000K Warm White	5000x8mm	DC12V	12W>	18-23lm
LSTR1-20-120C6K			6000K White				18-23lm
LSTR1-65-120C3K	SMD2835 IP65	120pcs / M	3000K Warm White	5000x8mm	DC12V	12W>	18-23lm
LSTR1-65-120C6K			6000K White				18-23lm
LSTR1-65-120-"X"			Red/Green/Blue				18-23lm
LSTR1-20-120C3K or C6K	SMD2835 IP20 (5mm wide for smaller profile)	120pcs / M	3000K / 6000K	5000x <b>5mm</b>	DC12V	12W>	18-23lm
<b>12V 204 to 240Leds/Mtr SMD2835</b>							
LSTR1-20-204 (C3K/C6K)	SMD2835 IP20	204pcs / M	3000K/6000K	5000x <b>10mm</b>	DC12V	16W>	16-18lm
LSTR1-65-240C6K	SMD2835 IP65	240pcs / M	6000K	5000x <b>17mm</b>	DC12V	24W>	16-18lm
Model No	LED Type	LED Qty	Color	Per Pack Length x Width	Voltage	Power (per mtr)	Lumen per Chip
<b>12V 60-120Leds/Mtr SMD5050 3000K-6000K/RGB/RGBW</b>							
LSTR2-20-60(C3K/C6K)	SMD5050 IP20	60leds/mtr	3000K/6000K	5000x10mm	DC12V	12W>	32-36lm
LSTR2-20-60RGB	SMD5050 IP20		RGB				32-36lm
LSTR2-65-60RGB	SMD5050 IP65		RGB				32-36lm
LSTR2-65-60"x"	SMD5050 IP65		"x" =R/G/B/Y				32-36lm
LSTR2-65-120RGB	SMD5050 IP20	120leds/mtr	RGB			16W>	32-36lm
LSTR2-65-60RGBW	SMD5050 IP65	60leds/mtr	<b>RGBW</b>			14W>	32-36lm
<b>Note: "x" - R - Red, G - Green, B - Blue, Y - Yellow</b>							
<b>24V in 10mtr SMD2835/SMD5050 Strip</b>							
LSTR1-20-24V120C3K	SMD2835 IP20	120pcs / M	3000K Warm White	10000x8mm	DC24V	14W>	16-18lm
LSTR1-20-24V120C6K			6000K Day White				
LSTR2-20-24V60RGB	SMD5050 IP20	60pcs / M	RGB	10000x10mm			32-36lm

Model No	LED Type	LED Qty	Color	Per Pack Length x Width	Voltage	Power (per mtr)	Test Data <b>0.5mtr</b>
<b>12V/24V 120 to 204Leds/Mtr SMD3014</b>							
LSTR3-20-12V204C3K	12V SMD3014 IP20	204pcs / M	3000K or 6000K White	5000x <b>10mm</b>	<b>DC12V</b>	16.0W>	14-16lm
LSTR3-20-12V204C6K							
LSTR3-20-24V204C3K	24V SMD3014 IP20	204pcs / M	3000K Warm White	5000x <b>10mm</b>	<b>DC24V</b>	19.0W>	16-18lm
LSTR3-20-24V204C4K			4000K Warm Cool				16-18lm
LSTR3-20-24V204C6K			6000K Day White				16-18lm
<b>24V 120Leds/Mtr SMD5630</b> 							
LSTR4-20-120C3K	24V SMD5630 IP20	120pcs / M	3000K Warm White	5000x <b>12mm</b>	<b>DC24V</b>	20.6W>	34-38lm
LSTR4-20-120C4K			4000K Warm Day				
LSTR4-20-120C6K			6000K White				
LSTR4-65-120C4K	24V SMD5630 IP65	120pcs / M	4000K Warm Day	5000x <b>12mm</b>	<b>DC24V</b>	20.6W>	
LSTR4-65-120C6K			6000K White				
<b>Special LED Strip - Magic Strip SMD5050 with WS2811 IC</b>							
LSTR-Magic60-IP67		5mtr LED SMD5050 60leds/mtr IP67 with WS2811 IC 12V DC					
LSTR-Magic120-IP67		5mtr LED SMD5050 120leds/mtr (double row) IP67 with WS2811 IC 12V DC					
LSTR-Magic-IR-1	Infra red controller with 24keys Remote						
LSTR-Magic-RF-1	SYNC Type	Radio Frequency Magic Strip Controller with Remote					
<b>Special LED Strip - Meat Display SMD5050- UV for Killing Germs / Meat Display Color</b>							
LSTR2-65-UV	SMD5050 IP65	60pcs / M	Ultra Violet for Killing Germs	5000x10mm	DC12V	12W>	26-28lm
LSTR2-65-MEAT	SMD5050 IP65	60pcs / M	Special Pink for Meat to Look Fresh	5000x10mm	DC12V	12W>	26-28lm
<b>Special RIGID LED Strip - Bakery 4000K</b>							
LPRO-RIG-2835		760mm LED Rigid Strip in SMD2835 Superbright Chip - 4000K					
LPRO-RIG-ACC1		6 Ways Terminal with DC Adaptor					
LPRO-RIG-WIRE1		200mm Wire for Rigid Strip connection					
<b>Special LED Rigid Strip - Growth Light for Plants or Flowers</b>							
LPRO-RIG-2835	Size:15x48x21mm, 56Leds,806lm, Per Bar 12W 24VDC						

Model No	LED Type	LED Qty	Color	Per Pack Length x Width	Voltage	Power (per mtr)	Lumen per Chip
 <b>12V DC Neon Flexible Strip IP65</b> 		<b>LSTRNF-X25 Series - 25mm Cutting Length (Single Color) 12V DC. Normal End Cap for Termination</b>					
LSTRNF-X612	SMD2835 IP65 Size:6(w)x12(h)	120pcs / M	"X" - 3000K/6000K/ Pink	<b>Price Per Mtr without Wire Tail</b>	<b>DC12V</b>	<b>&gt;12.0W</b>	<b>960lm</b>
LSTRNF-X816	SMD2835 IP65 Size:8(w)x16(h)	120pcs / M	"X" - 3000K/6000K				
LSTRNF-X	SMD2835 IP65 Size:8(w)x16(h)	120pcs / M	"X" - Blue/Ice Blue / Ice Green / Yellow / Orange / Pink				
Custom Cut Length	Custom Made Length with standard 50mm 2 core wire - <b>Price Per Termination</b>						
Custom Cut Length	Custom Made Length with 200-500mm 2 core wire - <b>Price Per Termination (extra \$1.20+gst per mtr)</b>						
  <b>12V DC Neon Flexible Strip IP65</b> 		<b>LSTRNF-X10 Series - 10mm Cutting Length (Single Color) 12V DC. Normal End Cap for Termination</b>					
LSTRNF-X10-816	SMD2835 IP65 Size:8(w)x16(h)	120pcs / M	"X" - 3000K/6000K				
LSTRNF-X10-816	SMD2835 IP65 Size:8(w)x16(h)	120pcs / M	"X" - Blue/Ice Blue / Ice Green / Yellow / Orange / Pink				
LSTRNFX-ACC-1A				Metal Clip. Size: L50xH18xW12mm			
LSTRNFX-ACC-1B	Plastic Clip			Plastic Clip. Size: L50xH12xW11mm			
LSTRNFX-ACC-1C	End Cap (Silicone)			For LSTRNF-X Series only			
<b>LSTRNF-X2RGB -8(w)x16(h)mm 25mm Cutting Length 12VDC. No Need Connector</b>							
LSTRNF-X2RGB	SMD5050 IP65 Size:8(w)x16(h)mm	60pcs / M	RGB	<b>Price Per Mtr without Wire Tail</b>	<b>DC12V</b>	<b>&gt;12.0W</b>	<b>32-36lm</b>
Custom Cut Length	Custom Made Length with standard 50mm 4 core wire - <b>Price Per Termination</b>						
Custom Cut Length	Custom Made Length with 200-300mm 4 core wire - <b>Price Per Termination</b>						
<b>LSTRNF-X1RGB -8(w)x16(h)mm 50mm Cutting Length 24VDC. No Need Connector</b>							
LSTRNF-X1RGB	SMD5050 IP65 Size:8(w)x16(h)mm	60pcs / M	RGB	<b>Price Per Mtr without Wire Tail</b>	<b>DC24V</b>	<b>&gt;12.0W</b>	<b>32-36lm</b>
Custom Cut Length	Custom Made Length with standard 50mm 4 core wire - <b>Price Per Termination</b>						
Custom Cut Length	Custom Made Length with 200-300mm 4 core wire - <b>Price Per Termination</b>						
<b>Magic Neon: 12(w)x20(h)mm 100mm Cutting Length (Magic RGB ). Normal End cap for termination</b>							
 LSTRNF-XCMRGB	SMD5050 IP65 Size:12(w)x20(h)mm	80pcs / M	IC RGB	<b>Price Per Mtr without Wire Tail</b>	<b>DC24V</b>	<b>&gt;14.0W</b>	<b>1020lm</b>
Custom Cut Length	Custom Made Length with standard 50mm 3 core wire - <b>Price Per Termination</b>						
Custom Cut Length	Custom Made Length with 200-300mm 3 core wire - <b>Price Per Termination</b>						





















Model No	LED Type	LED Qty	Color	Per Pack Length x Width	Voltage	Power (per mtr)	Lumen per Chip
<b>Magic Neon: 15(Dia) Round 340° light up 100mm Cutting Length (Magic RGB ).</b>							
 LSTRNF-RND-MRGB	SMD5050 IP65 Size:15(dia)mm	80pcs / M	IC RGB	Price Per Mtr without Wire Tail	DC24V	>14.0W	1020lm
Custom Cut Length	Custom Made Length with standard 50mm 3 core wire - <b>Price Per Termination</b>						
Custom Cut Length	Custom Made Length with 200-300mm 3 core wire - <b>Price Per Termination</b>						
Sync Magic Neon Controller+ RF Remote (Multiple controller with 1 remote)							
<b>LED for Signage - Rigid Module Strip / LED with 160° Lens</b>							
LSTRMOD-C3K	<b>Rigid Module</b> 	3pcs LED per Cluster	Warm 3000K	Module: 80(l)x18(w)mm. Wire: 85mm	12V DC	1.5W /Modular	125lm
LSTRMOD-C6K		3pcs LED per Cluster	Cool 6000K				130lm
LSTRMOD-LENS1x6C6K - 6pcs LEDs' Per Rigid Cluster	<b>LED with 160° Lens</b>  	6000K with CRI>80 Using 160° Lens with 40-50mm> with no hot spots. Two sided connecton wire and two led's cutting length.	Per Cluster: 500(l)x18(w)x2(t hick)mm. LED Spacing:82mm. Wire Spacing: 93mm. <b>Full 10length Size: 500(w)x900(l)m m</b>	24V DC	<b>6.0W per Length (6 leds /lgth)</b>	540lm per Cluster	
LSTRMOD-LENS10x6C6K 6pcs LEDs' Per Rigid Cluster x 10 Cluster's							
Model No	Description						
<b>LED Driver in 12V / 24V or Weatherproof - 2 Years Warranty</b>							
LSTR-TX-24		12V2A DC 24W	with DC adaptor & 1.0mtr flex & plug	Suitable up to 2 mtr of SMD5050/60 LEDs Strip			
LSTR-TX-72		12V6A DC 72W	with DC adaptor & 1.0mtr flex & plug	Suitable up to 5 mtr of SMD5050/60 LEDs Strip Size: 126(l)x56(w)x32(h)mm			
LSTR-TX-120		12V10A DC 120W	with DC adaptor & 1.0mtr flex & plug	Suitable up to 10 mtr of SMD5050/60 LEDs Strip Size: 170(l)x63(w)x40(h)mm			
LSTR-TX24V-72		24V3A DC 72W	with DC adaptor & 1.0mtr flex & plug	Suitable up to 3 mtr of SMD3014/204 LEDs Strip Size: 126(l)x56(w)x32(h)mm			
LSTR-TX24V-120		24V5A DC 120W	with DC adaptor & 1.0mtr flex & plug	Suitable up to 5 mtr of SMD3014/204 LEDs Strip Size: 170(l)x63(w)x40(h)mm			
LSTR-TXI-120W-12V	Industrial Type	12V DC 120W	without flex & plug	Size: L150xW70xH30mm			
LSTR-TXI-MW200W-12V	<b>Mean Well</b> -Industrial Type 	12V DC 200W	without flex & plug	Size: L200xW100xH30mm			

Model No	Description			
LSTR-TXI-MW350W-12V	<b>Mean Well</b> -Industrial Type 	12V DC 350W	without flex & plug	Size: L200xW100xH30mm
LSTR-TXI-350W-24V		24V DC 350W	without flex & plug	Size: L200xW100xH30mm
LSTR-TX-5W		12V DC 5W	without flex & plug	Suitable up to 5W 12V DC Lamp
LSTR-TX-10W	OMNI Driver Non Dim	12V DC 12W	without flex & plug	Suitable up to 12W 12V DC Lamp
LSTR-TXIP-CU-100W		12V DC 100W	without flex & plug	100W IP65 Outdoor LED Driver
LSTR-TXIP-CU-150W	<b>Eco Pwr</b> 	12V DC 150W	without flex & plug, 2 output wire	150W IP67 Outdoor LED Driver(2years Warranty)
LPV-60-IP67-MW60W	<b>Mean Well</b> 	12V DC 60W	without flex & plug, 1 output wire	60W IP67 Outdoor LED Driver (3years Warranty)
LPV-100-IP67-MW100W	<b>Mean Well</b> 	12V DC 100W	without flex & plug, 1output wire	100W IP67 Outdoor LED Driver (3years Warranty)
LPV-150-IP67-MW150W	<b>Mean Well</b> 	12V DC 150W	without flex & plug, 1 output wire	150W IP67 Outdoor LED Driver (3years Warranty)
LSTR-TXIP65-MW200W	<b>Mean Well</b>	12V DC 200W	without flex & plug	200W IP67 Outdoor LED Driver
LSTR-TXIP65-24VMW150W	<b>Mean Well</b> 	24V DC 150W	without flex & plug	150W IP67 Outdoor LED Driver <b>24V DC</b>
LSTR-TXIP-CU-60WDIM	<b>Dimmable</b> 	12V DC 60W	without flex & plug	60W IP65 Outdoor LED Driver
LSTR-TXIP-MW0-10V	<b>0-10v Dimmable Driver 120w</b>	12V DC 120W	without flex & plug	60W IP65 Outdoor LED Driver
LSTR-TXIP-AZ-12V	<b>5 in 1 Dimmable Driver 60w</b>	12V DC 60W	without flex & plug	60W IP65 Outdoor LED Driver
<b>Accessories / Controller for LED Strip</b>				
LSTR-ACC-1A		Female DC Adaptor		With 30mm wire
LSTR-ACC-2A		Male DC Adaptor		With 30mm wire
LSTR-ACC-3A		1 Female + 4 Male		For LED Driver

Model No	Description		
<b>Accessories / Controller for LED Strip</b>			
LSTR-ACC-1B		Female DC Adaptor	One End for Cable Termination and Other End to LED Driver
LSTR-ACC-2B		Male DC Adaptor	One End for Cable Termination and Other End to LED Driver
LSTR-ACC-3B		Female Push Type DC Adaptor	One End for Cable Termination and Other End to LED Driver
LSTR-ACC-1C		10mm Mounting Clip IP20 with 30mm wire	Suitable for IP20 LED Strip
LSTR-ACC-2C		10mm Mounting Clip IP65 with 30mm wire	Only Suitable for IP65 LED Strip
LSTR-ACC-3C		10mm Mounting Clip IP20 straight join	Only Suitable for IP20 LED Strip
LSTR-ACC-4C		10mm Mounting Clip IP65 straight join	Only Suitable for IP65 LED Strip
LSTR-ACC-5C		8mm / 10mm Mounting Clip IP20 with 30mm wire	Suitable for IP20 LED Strip
LSTR-ACC-1D		RGB Adaptor with Clip	For IP20 RGB Strip
LSTR-ACC-2D		RGB Adaptor with Pin	For RGB Strip
LSTR-ACC-3D		RGB Adaptor Click Type	For IP20 RGB Strip
LSTR-ACC-1E		RGB Adaptor with Clip	For RGB Strip
LSTR-ACC-2E		T Shape / L-Shape RGB Connector	For RGB Strip
LSTR-ACC-3E		T Shape / L-Shape / Cross Shape RGB Connector	For RGB Strip
LSTR-ACC-4E		L-Shape RGB Connector (Available in July)	For IP20 RGB Strip
LSTR-ACC-5E		Straight Wire to Strip RGB Connector (Available in July)	For RGB Strip 
LSTR-ACC-4E		L-Shape RGB Connector	For IP20 RGB Strip
LSTR-ACC-1F		1 to 3 RGB Strip C	For RGB Strip
LSTR-ACC-2F		4 Wire (custom cut length)	Pricing is per meter

Model No	Description		
<b>Controller for LED Strip</b>			
LSTR-CTR-DIM1S-IR		Infra Red: Controller + 24keys Remote Control	For Single Color Strip
LSTR-CTR-DIM1S-RF		RF Controller + 24keys Remote Control	For Single Color Strip
LSTR-CTR-RGB		Infra Red: RGB Controller + 44keys Remote Control	For RGB Strip
LSTR-CTR- <b>RGBW</b>		Infra Red: RGBW Controller + 44keys Remote Control	For RGBW Strip
LSTR-CTRRF-RGB1		RF (Radio Frequency): 12V/24V RGB or Single Color Controller. 6Ax3Channel.	For Single Color or RGB Strip
LSTR-CTRRF-RGB-SYNC		RF (Radio Frequency): 12V/24V RGB or Single Color Radio Frequency Sync and Programmable Controller. 6Ax3Channel.	<b>NEW!!!</b> Programmable Controller (Unlimited Controller using One Remote Control)
LSTR-CTRRF- <b>MULTI</b> -SYNC		RF (Radio Frequency): 12V/24V RGBW/RGB/CWCW Sync within 10mtr range (wireless) and Programmable Controller. 6Ax3Channel. With 4 Zone Remote	<b>NEW!!!</b> Programmable Controller (Unlimited Controller using One Remote Control)
LSTR-CTRRF- <b>RGBW</b> -SYNC		RF (Radio Frequency): 12V/24V RGBW Radio Frequency Sync and Programmable Controller. 6Ax3Channel.	<b>NEW!!!</b> Programmable Controller (Unlimited Controller using One Remote Control)
LSTR-CTRW1 (Black or White)		Touch: 12V/24V RGB or Single Color Wall Type Controller. 4Ax3Channel.	 86mm
LSTR-CTRW2		Touch: 12V/24V RGB or Single Color Wall Type Controller. 4Ax3Channel.	
LSTR-CTRWFIFIM-RGB		Wifi: 12V/24V RGB WIFI Controller (Control via iPhone or Android Phone)	For RGB Strip SMD5050 Support up to 8mtr length
LSTR-CTR-MTOUCH		Touch (Silver): 12V/24V for On/Off and Dimming	For Single Color Strip
LSTR-CTR-MWAVE		Wave (Black): 12V/24V with Wave (5mm away) on/off only	For Single Color Strip
LSTR-CTR-MDOOR		12V/24V Sensor (Door Open / Door Close) for On/Off	For Single Color Strip



Model No	Description		
LSTR-CTRSEN1		Motion Sensor for On/Off	Adjustable timer up to 10min 
<b>Aluminium Extrusion (Profile) for LED Strip</b>			
LPRO-0910		2.0M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover. Size: 9(w) x 10(h)mm	
LPRO-1708		2.0M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover. Size: 17(w) x 8(h)mm	
LPRO-1715		2.0M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover. Size: 17(w) x 15(h)mm	
LPRO-1806		<b>Bendable Horizontal Only</b> 2.0M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover. Size: 18(w) x 8(h)mm	
LPRO-01-Bracket		Angle Metal Bracket LPRO-01AS	
<b>Recessed Type</b> LPRO-28-1708		2.0M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover. Size: 23(w) Top x 18(w) Bottom x 14(h)mm. <b>Also Available in Black Lip</b>	
<b>Round Type</b> LPRO-RND20		2.0M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover. Size: 20mm(dia) .	
<b>TriangleType</b> LPRO-TR1919		2.0M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover.	
<b>TriangleType</b> LPRO-G1616		2.0M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover.	
<b>Surface Tall Diffuser</b> LPRO-2121		2.0M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover. Size: 21mm x 21mm. <b>Also Available in Black</b>	
LPRO-STEP59210		2.0M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover. Size: 59.4(w)x21.4(h)mm. Complete with End Cap.	
LPRO-5032		1.25M LED Aluminum Extrusion/ Profile ONLY, With Diffused cover. Size: 50(w)x32(h)mm. Complete with End Cap	